

Road King Crimson HD Total Concentrate



MATERIAL SAFETY DATA SHEET

Section 1

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product/Chemical Name: Road King Crimson HD Total
Product Description: Ethylene Glycol Based Antifreeze
Chemical Family: Inhibited Ethylene Glycol
CAS Registry: Mixture

Manufacturer: Innovative Fluids, LLC
916 Huber Drive
Monroe, MI 48162
734-241-5699

Section 2

COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	CAS No	WT. RANGE %	EXPOSURE LIMIT
*1,2-ethanediol (Ethylene Glycol)	107-21-1	>95%	50ppm Ceiling-ACGIH
Water	7732-18-5	<4%	Not applicable
Sodium Nitrite	7632-00-0	<1%	Not applicable
Potassium Hydroxide Solution	1310-58-3	<1%	2 mg/m ³ Ceiling
Sodium Benzoate	532-32-1	<1%	Not applicable
Sodium Molybdate Dihydrate	10102-40-6	<1%	Not applicable
Proprietary Inhibitors	Not applicable	<1%	Not applicable
Dye	Not applicable	<0.1%	Not applicable

*Hazardous according to OSHA (1910.1200) or one or more state Right-to-Know lists.

Section 3

HAZARDOUS IDENTIFICATION

Health: 2
Flammability: 1
Reactivity: 0
Special: None
0 = minimal 1= slight 2=moderate 3= serious 4= severe

Route(s) of Entry

Inhalation: Yes

Hazard Rating

	HMIS
Health:	2
Flammability:	1
Reactivity:	0
Personal Protection:	C

†Sec. 8

Skin: Yes
Ingestion: Yes
Eyes: Yes
Target Organs: Kidneys and Liver

Effects of overexposure:

Acute: **Eyes:** May cause minimal irritation, experienced as temporary discomfort.

Skin: Brief contact is not irritating. Prolonged contact, as with clothing wetted with material may cause defatting of skin or irritation, seen as local redness with possible mild discomfort. Other than the potential skin irritation effects noted above, acute (short term) adverse effects are not expected from brief skin contact.

Inhalation: Vapors or mist, in excess of permissible concentrations, or in unusually high concentrations generated from spraying, heating the material or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea, and drowsiness. Prolonged or repeated overexposure may result in the absorption of potentially harmful amounts of material.

Ingestion: Contains ethylene glycol and/or diethylene glycol, which are toxic when swallowed. A lethal dose for an adult is 1-2 ml per kilogram, or about 4 ounces (one-half cup). Symptoms include headache, weakness, confusion, dizziness, staggering, slurred speech, loss of concentration, faintness, nausea and vomiting, increased heart rate, decreased blood pressure, difficulty breathing and seeing, pulmonary edema, unconsciousness, convulsions, collapse and coma. Symptoms may be delayed. Decreased urine output and kidney failure may also occur. Severe poisoning may cause death. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Sensitization Properties: Unknown

Signs and Symptoms of Exposure: See above "Effects of Overexposure."

Medical Conditions Generally Aggravated by Long-Term Exposure: Repeated overexposure may aggravate existing kidney disease.

Section 3 HAZARDOUS IDENTIFICATION

Chronic Effects: Repeated ingestion may cause kidney damage

Carcinogenicity
NTP: Not listed
IARC Monographs: Not listed
OSHA Regulations: Not listed
ACGIH Not listed


Section 4 FIRST AID MEASURES

Emergency and First Aid Procedures:
Eye contact: Immediately flush with large quantities of water for at least 15 minutes

Skin contact:	Remove excess with cloth or paper towel. Wash thoroughly with soap and water. If irritation persists, get medical attention.
Ingestion:	Immediately contact a physician, poison control center or emergency treatment center. DO NOT induce vomiting. Aspiration Hazard: Product may be inhaled into lungs if vomited.
Inhalation:	Remove to fresh air. Restore and/or support breathing as required. Keep victim warm and at rest.
Note to Physicians:	Treat symptomatically
Special Precautions/Procedures:	None known

Section 5 FIRE-FIGHTING MEASURES

Unusual Fire Fighting procedures:	None known
Flash Point:	None detected
Flash Point Method:	Not applicable
Burning Rate:	Not applicable
Autoignition Temperature:	Does not apply
Flammable limits in air (% by volume):	
LEL:	Not determined
UEL:	Not determined
Flammability Classification:	Does not burn, but can emit fumes in a fire.
Extinguishing Media:	Use water spray, dry chemical, foam or carbon dioxide to extinguish.
Unusual Fire or Explosion Hazards:	None known
Fire-Fighting Instructions;	According to the National Fire Protection Association Guide, use water spray, dry chemical, foam or carbon dioxide. Water or foam may cause frothing. Use water spray to disperse the vapors and to provide protection for person attempting to stop the leak.
Fire-Fighting Equipment:	Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.
Unusual Fire Fighting procedures:	Not required
Other Information:	Products evolved when subjected to heat or combustion: Carbon Monoxide and Carbon Dioxide may be formed on burning in limited air supply.



Section 6 ACCIDENTAL RELEASE MEASURES

Spill/Leak Procedures: Ventilate area. Avoid breathing vapor. Wear appropriate personal protective equipment, including appropriate respiratory protection. Contain spill if possible. Wipe up or absorb on suitable material and shovel up. Prevent entry into sewers and waterways. Avoid contact with skin, eyes or clothing.

Regulatory Requirements: If more than 10,539 pounds of product is spilled, then report spill according to SARA 304 and/or CERCLA 102(a) requirements, unless product qualifies for petroleum exemption (CERCLA Section 101 (14)).

Section 7 HANDLING AND STORAGE

Handling Precautions Minimum feasible handling temperatures should be maintained.

Storage Requirements: Periods of exposure to high temperature should be minimized. Water contamination should be avoided.

ETHYLENE GLYCOL BASE – Ethylene Glycol has produced birth defects in rodents. Do not store near food.

Section 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: Normal to maintain exposure below TLV

Permissible Concentrations in Air: 10mg/cubic meter for particulate mist; 50 ppm (125 mg/cubic meter) ceiling limit for Ethylene Glycol (ACGIH 1984-1985)

Respiratory Protection: Supplied air respiratory protection for cleaning large spills or upon entry into tanks, vessels, or other confined spaces. Use a NIOSH approved organic vapor and gas respirator with mist filter.

Eye Protection: Chemical type goggles or face shield optional.

Protective Clothing/Equipment: Wear chemically protective gloves, boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles.

Work and Hygienic Practices: Exposed employees should exercise reasonable personal cleanliness; this includes cleansing exposed skin areas several times daily with soap and water, and laundering or dry cleaning soiled work clothing at least weekly.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9**PHYSICAL AND CHEMICAL PROPERTIES**

Appearance and odor:	Mild odor, may contain dye in one of several colors.
Boiling Point (760 mm Hg):	317°F
Freezing/Melting Point:	-3°F
Specific Gravity (water =1):	1.110-1.125
Vapor Density (air =1):	1.8
Percent Volatile by Volume:	NIL
Refractive Index:	1.4300
Solubility in Water (% by wt):	Soluble
Vapor Pressure (at 20°C):	18mm Hg.
pH:	8.8-10.0
Viscosity SUS @ 100°F	Less than 20cst

Section 10**STABILITY AND REACTIVITY**

Stability:	Stable
Polymerization:	Does not occur
Chemical Incompatibilities:	Strong oxidizers
Conditions to Avoid:	High temperatures above 413°C (775°F) (product can decompose)
Hazardous decomposition products:	Carbon dioxide, carbon monoxide

Section 11**TOXICOLOGICAL INFORMATION**

Eye Effects:	Believed to cause slight eye irritation.
Skin Effects:	Can be irritating to skin upon prolonged contact
Acute Inhalation Effects:	Drowsiness, narcosis, and unconsciousness possible upon exposure to high concentrations in poorly ventilated confined spaces.
Acute Oral Effects:	Can cause irritation to mouth, throat and stomach
Chronic Effects:	Liver and kidney damage in a 2 year rat feeding study using 1-2% Ethylene Glycol. Oral administration of very high doses of Ethylene Glycol produced birth defects in laboratory animals.
Carcinogenicity:	Neither product nor its ingredients are listed by IARC, NTD or OSHA
Mutagenicity:	Not mutagenic
Teratogenicity:	Not Teratogenic

Section 12**ECOLOGICAL INFORMATION**

Ecotoxicity:	Oral:	Believed to be 4.7-8.5 g/kg (rat); moderately toxic
	Inhalation:	Not determined.
	Dermal:	Believed to be 1-3 g/kg (rabbit); slightly toxic

Other: Not determined.

Irritation Index/Estimation of Irritation (Species)

Skin: Believed to be 0.5-1.8/8.0 (rabbit); slightly irritating

Eyes: Believed to be 15-25/110 (rabbit); slightly irritating

Soil Absorption/Mobility: Not determined

Section 13 DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of waste in accordance with Federal, State and Local laws.

Disposal Regulatory Requirements: Under RCRA, it is the responsibility of the user of products to determine, at the time of disposal, whether product meets RCRA criteria for hazardous waste. This is because product uses transformations, mixture, processes, etc., may render the resulting material hazardous (see waste classification)

Container Cleaning and Disposal: Containers should be cleaned of residual product before disposal, and disposed of in accordance with all applicable laws and regulations.

Section 14 TRANSPORT INFORMATION

DOT Shipping Name: Not applicable
Shipping Symbols: Not applicable
Hazard Class: Not applicable
DOT Identification No.: Not regulated unless shipping container holds at least 10,539 pounds.
Packing Group: Not applicable
Label: Not applicable
Special Provisions (172.102): Not applicable

Packaging Authorizations

a) Exceptions: Not applicable
b) Non-bulk Packaging: Not applicable
c) Bulk Packaging: Not applicable

Quantity Limitations

a) Passenger, Aircraft, or Railcar: Not applicable
b) Cargo Aircraft Only: Not applicable

Vessel Stowage Requirements

a) Vessel Stowage: Not applicable
b) Other: Not applicable

MSDS: Road King Crimson HD Total Concentrate
Item Number: 9901RED

Section 15**REGULATORY INFORMATION****EPA Regulations**

RCRA Hazardous Waste Number and

RCRA Hazardous Waste Classification: Unused product is not classified as a hazardous waste by RCRA criteria

CERCLA Hazardous Substance and CERCLA

Reportable Quantity: Does not contain any ingredients listed as a CERCLA hazardous substance.

SARA Toxic Chemical and SARA EHS:

Contains following substance which is listed in Title III: Ethylene Glycol.

SARA 313 Information:

SARA Hazard Category: An immediate health hazard A delayed health hazard

OSHA Regulations:**State Regulations:****Other:** All components listed on both TSCA (USA) and DSL (Canada) inventory.**Section 16****OTHER INFORMATION****Prepared By:** Innovative Fluids, LLC.**Additional Hazard Rating Systems:** None**Disclaimer: THE INFORMATION GIVEN HEREIN IS GIVEN IN GOOD FAITH AND FROM SOURCES WE BELIEVE RELIABLE. BUT NO WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS IS MADE.**

The conditions or methods of handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not apply.

Issue: New
Approval Date: December 3, 2008
Supercedes Date: New
Rtn Number: 9901RED (Official Copy)

CONSULT: Innovative Fluids, LLC. FOR FURTHER INFORMATION.